

Personal Airline System PAS Colt



Visit: www.thesafetyequipmentstore.com Or Email: besafe@thesafetyequipmentstore.com for Sales & Service.

Combining versatility, ease of use and the latest in breathing apparatus design, Draeger's Personal Airline System, the PAS Colt is among the most technologically advanced short duration and emergency escape units available.

The PAS Colt is a Supplied Airline Respirator (Combination Pressure Demand, Type "C") with a 5 or 10-minute self-contained air cylinder for emergency use. The PAS Colt, is NIOSH approved for entry and escape, and may be used in the supplied air mode up to 300 feet or 12 hose length sections from the air source, whichever is greater.

The very latest harness design and materials, accompanied by lightweight cylinders, make wearing the ergonomically designed PAS Colt stable and comfortable. The versatility allows it to be used effectively in applications and environments ranging from chemical spills and decontamination operations to routine maintenance tasks.

The PAS Colt is a hip-mounted unit with a distinctive, sophisticated harness design which retains its form, making it easy for the wearer to don the apparatus simply and quickly.

The procedure for donning the apparatus is evident at first glance, even to the inexperienced user. Equipped with a unique 'drop down' feature where the cylinder can be un-clipped from the waistbelt, makes the PAS Colt ideal for use in confined space entry applications. The harness has been constructed using an anti-static material inert to chemicals and oil, and impervious to most acids and alkalis. Benefiting from a high resistance to abrasion and heat, this new harness meets the requirements of EN137 heat and flame resistance. This means that the unit operates trouble free over a temperature range of -22°F to 140°F and will self-extinguish within 5 sec after exposure to flame temperature of 1742°F plus or minus 122°F. The Micro also is fully machine washable.

This material was chosen because of its flexibility and ability to retain its form and shape, in a wide range of temperatures. Its durability, ease of cleaning, resilience and strength means it is ideal for use in extreme conditions. The technology used in the development of this unit is inherited from Draeger's advanced PAS® range of breathing apparatus, designed for professional fire fighters. The buckles used are designed to be easily located, even when wearing gloves, for quick adjustment. The buckles follow the contours of the unit to reduce the risk of snagging.

Should the airline supply fail for any reason, the escape cylinder would be employed by simply opening the cylinder valve. **New to our SAR system is the optional Low Pressure Airline warning whistle which activates in the event that the incoming air pressure drops below safe levels.**

The PAS Colt includes the versatile Draeger Panorama Nova full facepiece with triple sealing edges for a superior fit, and a speech diaphragm for clear communications. Three sizes in one mask is also compatible with other Draeger compressed air respiratory products.

TECHNICAL DATA

	5 Minute Colt	10 Minute Colt
Unit Profile Aproximate	5.5" x 4.5" x 20"	5.75"x4.75"x22"
	13.97 x 11.43 x 50.8cm	14.60 x 12.06 x 55.88cm
Weight complete unit with mask without air (lbs)	10.0 pounds	11.3 pounds
	4.53 kg	5.12 kg
Mask Body Material	EPDM or Silicone	EPDM or Silicone
Harness Material	Closed cell Ethylene Vinyl Acetate	Closed cell Ethylene Vinyl Acetate
Airline Pressure (psig)	87 - 137	87 - 137
Cylinder Pressure (psig)	2216 Aluminum	3000 Hoop Wrap
Cylinder and Valve Weight - empty	4.7 lbs	5.5 lbs

ORDERING INFORMATION

COLT 5 Min 2216psi Work Unit with Mask Hansen Brass	4057539
COLT 5 Min 2216psi Work Unit w/o Mask Hansen Brass	4057540
COLT 10 Min 3000psi AL Work Unit with Mask Hansen Brass	4057541
COLT 10 Min 3000psi AL Work Unit w/oMask Hansen Brass	4057542

Installed Options

Installed Silicone mask	4055475
Installed 5 Min 2216 psi AL Cyl with SCBA Valve	*4057543
Installed Colt LP SAR Alarm, Hansen Brass	4057538
Installed Colt/Micro Hansen Stainless SAR Plug	4057604
Installed Colt/Micro Snaptite SAR Plug	4057605
Installed Colt/Micro Schrader SAR Plug	4057606
Installed Colt/Micro CEJN SAR Plug	4057607
Installed Colt/Micro foster Stainless SAR Plug	4057608

* this option Installs Cylinder Part Number 4057549 on the Colt for 5-minute unit only.

Spare Cylinders

5 min 2216psi Aluminum Cyl w/ Std. ALE Valve	4054744
5 min 2216psi Aluminum Cyl w/ SCBA Valve	4057549
10 min 3000psi Hoop Wrap Cyl w/ Std. ALE Valve	4054962

Storage/Carry Case

Case 5/10 minute 18.5x13.75x7.5 in (47x35x19cm)	4057541
┌	┐
└	┘

QUICK DISCONNECT COUPLINGS

Hansen Brass Socket and Union	4059247
Hansen Brass Plug and Nut	4059248
Hansen SSSocket and Union	4050835
Hansen SSPlug and Nut	4050836
Snaptite Socket and Union	4059251
Snaptite Plug and Nut	4059252
Schrader Socket and Union	4059249
Schrader Plug and Nut	4059250
Foster SSSocket and Union	4051993
Foster SSPlug and Nut	4051992
CEJN Socket and Union	4059253
CEJN Plug and Nut	4059254

LIGHT DUTY HOSE WITH THREADED CONNECTIONS

5' length Light Duty Airline Hose	4059357L
25' length Light Duty Airline Hose	4059061L
50' length Light Duty Airline Hose	4059062L
75' length Light Duty Airline Hose	4054854L
100' length Light Duty Airline Hose	4059063L

HEAVY DUTY HOSE WITH THREADED CONNECTIONS

5' length Heavy Duty Airline Hose	4059357
25' length Heavy Duty Airline Hose	4059061
50' length Heavy Duty Airline Hose	4059062
75' length Heavy Duty Airline Hose	4054854
100' length Heavy Duty Airline Hose	4059063

SUBSIDIARIES

DRAEGER SAFETY, INC.
101 Technology Drive
Pittsburgh, PA 15275-1057
USA
Tel 1-412-787-8383
Fax 1-412-787-2207
www.draeger.com

CUSTOMER SERVICE
Tel 1-800-858-1737
Fax 1-800-922-5519

TECHNICAL SERVICES
Tel 1-888-794-3806
Fax 1-888-794-3807

DRAEGER SAFETY CANADA LTD.
7555 Danbro Crescent
Mississauga, ON L5N-6P9
Canada
Tel 1-905-821-8988
Fax 1-905-821-2565

CUSTOMER SERVICE
Tel 1-877-372-4371
Fax 1-800-Fax-Tube

DRAEGER SAFETY S.A. DE C.V.
Av. Peñuelas No. 5
Bodega No. 37
Fraccionamiento Industrial San
Pedrito
Queretaro, Qro. C.P. 76148
Mexico
Tel 52-442-246-1113
Fax 52-442-246-1114