

Dräger Saver CF N (NIOSH) Emergency Escape Breathing Apparatus (EEBA)

In emergency situations, conditions can deteriorate rapidly. Ambient breathing air can be suddenly filled with smoke or toxic fumes and rapid escape is the only available option. The Dräger Saver CF N constant flow Emergency Escape Breathing Apparatus allows safe, effective and uncomplicated escape from hazardous environments.



WHEN TIME IS OF THE ESSENCE

Simple to don and easy to operate, this hood-based, positive-pressure breathing device can be used with minimal training. The Dräger Saver CF N is highly visible and was designed to be suitable even for people with spectacles or facial hair. When opened, the Dräger Saver is automatically activated and begins feeding a continuous supply of breathing air. The Saver gives the wearer the precious additional time needed to exit the area safely.

HIGHLY VISIBLE, EVEN UNDER ADVERSE CONDITIONS

Packaged in an integrated soft bag, the Saver can be easily wall-mounted in strategic locations in potentially hazardous areas. The bright orange bags feature reflective panels for enhance visibility, even under low lighting conditions. The Saver is compact and lightweight and can be worn either as a chest bag or over the shoulder. Made from highly resistant materials, it is washable, flame retardant and allows water to drain freely.

UP TO 15 MINUTES OF LIFESAVING AIR

The Dräger Saver utilizes a simple, failsafe reducer system with excellent flow characteristics, providing a consistent rate of air flow until the cylinder is completely empty. It can be equipped with cylinders which can hold either a 5, 10, or 15 minute supply of air. The flame-retardant hood incorporates a large visor for maximum peripheral vision.

LOW-MAINTENANCE PROTECTION

The Dräger Saver requires very little service or maintenance. A transparent window on the soft bag lets you check the cylinder pressure gauge easily without unpacking the unit. The cylinder can be refilled without the need to remove it from the bag.

CONFORMS TO RELEVANT STANDARDS AND NORMS

The Dräger Saver CF N complies with NIOSH, ABS and TC approvals. It can be used in a range of applications both on and off shore to protect the user against any unexpected change in environment. Chemical, oil & gas, shipping, steel and pharmaceutical industries can all rely on the Dräger Saver CF N for safe and uncomplicated escape.



Dräger Saver CF5 N, Saver CF10 N, and Saver CF15 N

DRÄGER SAVER CF NIOSH – FOR YOUR SAFE ESCAPE





TECHNICAL DATA

	Dräger Saver CF NIOSH 5 Minute	Dräger Saver CF NIOSH 10 Minute	Dräger Saver CF NIOSH 15 Minute
Dimensions (NIOSH) (H × D × L)	240 × 180 × 320 mm	240 × 180 × 440 mm	240 × 190 × 420 mm
Weight (kg)	3.980 kg	5.120 kg	5.450 kg
Cylinder charging pressure	3000 psi		
Airflow to the hood	35–37 L/min		
Operating temperature range	-15°C to +60°C		
Approvals	NIOSH, ABS and TC		

ORDER INFORMATION

Dräger Saver CF NIOSH	Part. no
Saver CF5 N	40 42 055
Saver CF10 N	40 42 056
Saver CF15 N	40 42 057

-

I

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany

www.draeger.com

Manufacturer:

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany

CANADA

Draeger Safety Canada Ltd. 2425 Skymark Ave Mississauga, Ontario, L4W 4Y6 Tel +1 905 821 8988 Toll-free +1 877 Drager 1 (+1 877 372 4371) Fax +1 905 821-2565 Toll-free Fax +1 800 329 8823

USA

Draeger Safety, Inc. 101 Technology Drive Pittsburgh, PA 15275 Tel +1 412 787 8383 Fax +1 412 787 2207

Customer Service Tel 800 858 1737 Fax 800 922 5519

Technical Service Tel 888 794 3806 Fax 888 794 3807